

싱크라운

4인치 감열식 바코드 라벨 프린터

SMP-L40

127mm/s의 빠른 인쇄 속도와 강력한 내구성

용지 폭 가이드가 탑재되어 38mm~120mm까지 용지 폭 조절 가능

다양한 인터페이스 지원 USB, RS232, 이더넷, 듀얼 블루투스

차량용 시거잭 어댑터 지원



작지만 빠른 출력,

127mm/s의 빠른 출력 속도,
217 * 182 * 172mm 사이즈,
1.4kg의 가벼운 무게를 자랑합니다.



다양한 라벨
사이즈 자동인식,

다양한 라벨의 크기를 자동으로 인식
해서 퀄리티 있는 인쇄가 가능합니다.



광범위한 호환성,

모바일 기기와 데스크톱, 차량까지
모두 호환이 가능한 제품입니다.

- True USB (스마트폰 출력가능)
- Dual Bluetooth (3.0 & 4.0)
- 차량용 시거잭 어댑터 (별도옵션)

다양한 인터페이스

1. USB
2. USB + Dual Bluetooth (3.0 & 4.0)
3. USB + Serial + Ethernet



SMP-L40

4인치 감열식 바코드 라벨 프린터



우편, 택배



떡집, 제과점



식자재 유통



대형마트



창고관리



병원, 약국



후면 급지 가능

택배용지 및 대용량 용지 공급시
후면에서 용지 공급이 가능합니다.



SMP-L40 구성품

본체, 사용자 퀵매뉴얼, 시리얼 케이블,
USB 케이블, 전원 어댑터, 전원 케이블

SPECIFICATIONS

4INCH DIRECT THERMAL
BARCODE LABEL PRINTER
SMP-L40

Performance Characteristics

Printing method : Direct Thermal

Resolution : 203dpi

Max printing width : 104mm

Printing speed : 127mm/s (5inch/s)

Interface : USB (standard)

USB + RS232 + Ethernet (option)

USB + Dual Bluetooth 3.0 & 4.0 (option)

Paper : Type : Tagboard, Continuation paper, Black mark paper

Label width : 38mm-120mm

Label height : Min 30mm~Max 300mm

Storage : RAM: 8M / Flash: 4M (expand memory 8M realizable)

Barcode : 1D : Code 39, Code 93, ITF, EAN 128, Code 128, subsets A, B,
C, Codabar, EAN-8, EAN-13, UPC-A, UPC-E, EAN and UPC 2(5),
digits, add-on, MSI, MSIC, PLESSEY, CPOST, ITF 14, EAN 14

2D : QR code

OS : Windows XP / Win 7 / Win 8 / Win10 / Android / iOS

Physical Characteristics

Detection sensor : Gap sensor, Paper End Sensor,
uncover sensor, black mark sensor

Power supply : Type : External power adaptor

Input : AC 100V-240V, 50-60HZ

Output : DC24V±5%, 2.5A

LED Indication : RGB LED

Command : TSC

Dimension : 217mm*182mm*170mm

Net weight : 1.4kg

TPH lifespan : 50km

User Environment

Operation Temperature : 0°C~50°C

Storage Temperature : -10°C~60°C

Components

Standard : Adaptor, Power cable, USB cable, Quick installation guide,
RS232 cable (Multi interface only)

Accessories : Paper tray (optional), Car Adapter (optional)

* 사양은 예고없이 변경 될 수 있습니다.

